



STANDARD EQUIPMENT:

- Leaf-type PTFE high efficiency filter, rated 99.9% efficient @ 1 micron, 30 sq. feet surface area
- Heavy Duty Manual Filter Shaker.
- Secondary filter cartridge located ahead of the pump.
- NEMA 4 Starter with thermal overload protection.
- Flexible electrical cord, 3 conductor, (without plug) x 25' lg
- Interchangeable 40-gallon collection container (holding capacity 450lbs.) with 4" dia. wheels
- Large 14" diameter front wheels for easy movement over uneven surfaces and expansion joints
- Dual 8" diameter swivel casters in the rear for easy maneuvering in tight areas
- Vacuum gage
- Vacuum relief valve
- Sound proofing for noise levels of less than 80 dbA at 10' @ 8"Hg

TECHNICAL DATA:

Continuous duty vacuum producer

Pump Positive Displacement, Rotary Lobe Motor TEFC, 1750 RPM, standard efficiency

Voltage 230V or 460V/60hz 3 ph (select at time of order)

Capacity of Container 40 gallon

Dimensions 66"L x 32"W x 68"H


Weight 1000 lbs.

Paint Blue powder coat

| PERFORMANCE | 10 HP | 15 HP |
|-----------------|-----------------------------|----------------------------|
| MAXIMUM AIRFLOW | 240 ACFM @ 12"Hg (162" H20) | 380 ACFM @ 12"Hg (162"H2O) |
| INLET SIZE | 2.5" CAMLOCK | 3.0" CAMLOCK |
| | | |




POWER



Positive Displacement, Rotary Lobe Vacuum Pump provides superb airflow performance at high vacuum. This gives you the ability to vacuum material easily from piles or long distances.

70 - 100% MORE VACUUM PLUS AIRFLOW

- **= LONGER DISTANCES**
- = TONS PER HOUR
- = FINISH THE JOB FASTER
- = BEST PRODUCTIVITY & R.O.I.





FEATURES

Leaf-type PTFE high efficiency filter, rated 99.9% efficient @ 1 micron. (Not Shown)

NEMA 4 Starter with thermal overload protection.



Secondary Safety filter cartridge located ahead of the pump. (HEPA Optional)

Dual 8" diameter swivel casters for easy maneuvering in tight areas (Not Shown)

Large 14" diameter front wheels for easy movement over uneven surfaces and expansion joints

VAC-U-MAX

MODEL 1020-MFS with Manual Filter Shaker






The 1020MFS is typically used with a material intercept: either a 55-gallon drum, or a forkliftable self-dumping hopper. The 55-gallon drum will allow access to confined areas, while a 1or 2 cubic yard hopper will offer up to 50 cubic feet of collection capacity.



The 1020MFS shown to the left is being used to reclaim Steel Shot and introduce it back into the customer's shot blast machine via a VAC-U-MAX Intercept Hopper.



VERSATILITY



The VAC-U-MAX MDL1020MFS is a versatile machine. It will collect just about anything! The 1020MFS can be used as a central vacuum source. It is common for a customer to install a tubing network in areas of their plant and connect our 1020MFS to the tubing header. VAC-U-MAX calls this a "breakaway" central vacuum, because the vacuum can be disconnected from the permanent tubing and moved about in its portable configuration. You can maximize your investment by rolling the 1020MFS where it's needed, and putting it to work.

VAC-U-MAX

Accessories & Optional Equipment



MDL 115-01 Heavy-duty Intercept Cover assembly for 55 gallon drums, complete with replaceable stainless steel inlet and outlet adaptors, internal impact baffle plate with replaceable rubber absorption flap, neoprene gasket with grounding strap, lifting handles, and carbon steel construction with blue powder coat finish.

#23861 Drum dolly, 55-gallon, heavy-duty steel spinning with (4) 4" swivel casters, and drum lock-down nuts, blue powder coat finish.

#23908 55-gallon open-top steel drum, 16-gauge, with 2" bung and blue powder coat finish.

2.5" Pick-up Tools



#21384

Beveled Rubber Hand Tool 2.5"

#03414

Suction Tube, 2.5" X 48" Long

3.0" Pick-up Tools



#21385



#03416 Suction Tube, 3.0" X 48" Long

60935 Bulk Wand 3.0"

2.5" ID Hose

| Vinyloy Hose | | |
|---------------|------------|-------|
| | 2.5" x 10' | 08541 |
| | 2.5" x 15' | 08544 |
| | 2.5" x 25' | 08547 |
| Abr-Flex Hose | | |
| | 2.5" x 10' | 52108 |
| | 2.5" x 15' | 52109 |
| | 2.5" x 25' | 52110 |

2 N" ID HOSE

| 3.0 ID 1103E | | |
|---------------|------------|-------|
| Vinyloy Hose | | |
| | 3.0" x 10' | 14983 |
| | 3.0" x 15' | 14984 |
| | 3.0" x 25' | 14985 |
| Abr-Flex Hose | | |
| | 3.0" x 10' | 52112 |
| | 3.0" x 15' | 52113 |
| | 3.0" x 25' | 52114 |

Suggested Spare Parts

| Description |
|----------------------------------------------------------|
| Spare PTFE Leaf- Type Filter, Part #42923 |
| Spare Secondary Filter Cartridge, Part #20184 |
| Spare Secondary HEPA Filter Cartridge, Part# 22483 |